

CERTIFICATE

No. U6 102263 0037 Rev. 00

Holder of Certificate: **Suzhou Cyantronic Technology Co., Ltd**
No.1 Shenxiang Road, SND
215151 Suzhou, Jiangsu
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product: **Electronic control gear for emergency lighting**
Emergency module

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 704022408130-00

Date, 2024-12-09


(Yin Ji)

CERTIFICATE

No. U6 102263 0037 Rev. 00

Model(s):

APRA03-30; APRA03-30/ST; APRA03-30/SS;
APRA03-30/DA; BEM303; BEM303/ST; BEM303/DA;
APRB03-30; APRB03-30/ST; APRB03-30/SS;
APRB03-30/DA; APRC03-30; APRC03-30/ST;
APRC03-30/SS; APRC03-30/DA.

Brand Name:

CYANTRONIC

CYANTRONIC

Parameters:

Rated voltage:	220-240V~
Rated frequency:	50/60Hz
Rated input current:	See model list
Rated output:	See model list
Rated duration:	See model list
tc:	75°C
Method of installation:	Built-in
Battery:	See model list

CERTIFICATE

No. U6 102263 0037 Rev. 00

Model list:

Model	Internal Code	Rated Input Current (mA)	Battery	Rated output				Duration (h)
				U _{rated} (VDC)	I _{emergency} (mA)	P _{rated} (W)	U-OUT (VDC)	
APRA03-30	9100330385	Max. 18	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
APRA03-30/ST	9100330386	Max. 18	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
APRA03-30/SS	9100330388	Max. 18	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
APRA03-30/DA	9100330387	Max. 18	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
BEM303	9120330385	Max. 18	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
BEM303/ST	9120330386	Max. 18	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
BEM303/DA	9120330387	Max. 18	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
APRB03-30	9110330385	Max. 18	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
APRB03-30/ST	9110330386	Max. 18	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
APRB03-30/SS	9110330388	Max. 18	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
APRB03-30/DA	9110330387	Max. 18	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
APRC03-30	9120330385	Max. 18	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
APRC03-30/ST	9120330386	Max. 18	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
APRC03-30/SS	9120330388	Max. 18	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
APRC03-30/DA	9120330387	Max. 18	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3

Tested according to:

EN 61347-1:2015/A1:2021
EN 61347-2-7:2012/A2:2022

Production Facility(ies):

102263