

CERTIFICATE

No. U6 102263 0047 Rev. 00

Holder of Certificate: **Suzhou Cyantronic Technology Co., Ltd**
No.1 Shenxiang Road, SND
215151 Suzhou, Jiangsu
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product: **Electronic control gear for emergency lighting**
Emergency module

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 704022409989-00

Date, 2025-01-24


(Yin Ji)

CERTIFICATE

No. U6 102263 0047 Rev. 00

Model(s):

ANI03-30/MC.; ANI01-30/MC; ANI01-30; ANI03-15/MC.;
ANI03-30.; ANI03-15.; ANI02-30LFP7302-S20;
ANI03-30/MC/ST.; ANI01-30/MC/ST; ANI01-30/ST;
ANI03-15/MC/ST.; ANI03-30/ST.; ANI03-15/ST.;
ANI03-30/MC/DA; ANI03-15/MC/DA; ANI03-30/DA;
ANI03-15/DA; ANI05-30/MC; ANI08-15/MC; ANI05-15/MC;
ANI05-30; ANI08-15; ANI05-15; ANI04-30LFP7304-S20;
ANI05-30/MC/ST; ANI08-15/MC/ST; ANI05-15/MC/ST;
ANI05-30/ST; ANI08-15/ST; ANI05-15/ST; ANI05-30/MC/DA;
ANI08-15/MC/DA; ANI05-15/MC/DA; ANI05-30/DA;
ANI08-15/DA; ANI05-15/DA; AI03-30/MC; AI03-15/MC;
AI01-30/MC; AI01-30; AI03-30; AI03-15; AI03-30/MC/ST.;
AI01-30/MC/ST; AI01-30/ST; AI03-15/MC/ST; AI03-30/ST.;
AI03-15/ST; AI03-30/MC/DA; AI03-15/MC/DA; AI03-30/DA;
AI03-15/DA; AI02-30LFP7302-S20; AI05-30/MC; AI05-15/MC;
AI05-30; AI05-15; AI05-30/MC/ST; AI05-15/MC/ST; AI05-30/ST;
AI05-15/ST; AI05-30/MC/DA; AI05-15/MC/DA; AI05-30/DA;
AI05-15/DA; AI04-30LFP7304-S20

Brand Name:

CYANTRONIC

CYANTRONIC

Parameters:

Rated voltage:	220-240V~
Rated frequency:	50/60Hz
Rated input current:	See model list
Rated output:	See model list
Rated duration:	See model list
tc:	75°C
Method of installation:	Built-in
Battery:	See model list

CERTIFICATE

No. U6 102263 0047 Rev. 00

Model list:

Model	Internal Code	Rated Input Current (mA)	Battery	Rated output				Duration (h)
				Ouput Voltage (VDC)	Iemergency (mA)	Prated (W)	U-OUT (VDC)	
ANI03-30/MC.	9010330365	Max. 19	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
ANI01-30/MC	9010130165	Max. 19	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
ANI01-30	9010330385	Max. 19	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
ANI03-15/MC.	9010310165	Max. 19	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	1.5
ANI03-30.	9010330385	Max. 19	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
ANI03-15.	9010310185	Max. 19	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	1.5
ANI02-30LFP7302-S20	9010330385	Max. 19	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
ANI03-30/MC/ST.	9010330366	Max. 19	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
ANI01-30/MC/ST	9010330366	Max. 19	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
ANI01-30/ST	9010330386	Max. 19	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
ANI03-15/MC/ST.	9010310166	Max. 19	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	1.5
ANI03-30/ST.	9010330386	Max. 19	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
ANI03-15/ST.	9010310186	Max. 19	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	1.5
ANI03-30/MC/DA	9010330367	Max. 19	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
ANI03-15/MC/DA	9010310167	Max. 19	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	1.5
ANI03-30/DA	9010330387	Max. 19	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	3
ANI03-15/DA	9010310187	Max. 19	2IFpR19/66 2.0Ah 6.4V	30-300	8-80	3	310	1.5
ANI05-30/MC	9010530465	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	30-300	13-130	5	310	3
ANI08-15/MC	9010810465	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	30-300	13-130	5	310	1.5
ANI05-15/MC	9010510365	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	30-300	13-130	5	310	1.5
ANI05-30	9010530485	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	30-300	13-130	5	310	3
ANI08-15	9010810485	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	30-300	13-130	5	310	1.5
ANI05-15	9010510385	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	30-300	13-130	5	310	1.5
ANI04-30LFP7304-S20	9010530485	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	30-300	13-130	5	310	3
ANI05-30/MC/ST	9010530466	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	30-300	13-130	5	310	3
ANI08-15/MC/ST	9010810466	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	30-300	13-130	5	310	3
ANI05-15/MC/ST	9010510366	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	30-300	13-130	5	310	1.5
ANI05-30/ST	9010530486	Max. 21	2IFpR19/66-2	30-300	13-130	5	310	3

CERTIFICATE

No. U6 102263 0047 Rev. 00

			4.0Ah 6.4V					
ANI08-15/ST	9010810486	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	30-300	13-130	5	310	1.5
ANI05-15/ST	9010510386	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	30-300	13-130	5	310	1.5
ANI05-30/MC/DA	9010530467	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	30-300	13-130	5	310	3
ANI08-15/MC/DA	9010810467	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	30-300	13-130	5	310	1.5
ANI05-15/MC/DA	9010510367	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	30-300	13-130	5	310	1.5
ANI05-30/DA	9010530487	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	30-300	13-130	5	310	3
ANI08-15/DA	9010810487	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	30-300	13-130	5	310	1.5
ANI05-15/DA	9010510387	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	30-300	13-130	5	310	1.5
AI03-30/MC	9000330365	Max. 19	2IFpR19/66 2.0Ah 6.4V	20-55	45-125	3	60	3
AI03-15/MC	9000310165	Max. 19	2IFpR19/66 2.0Ah 6.4V	20-55	45-125	3	60	1.5
AI01-30/MC	9000330365	Max. 19	2IFpR19/66 2.0Ah 6.4V	20-55	45-125	3	60	3
AI01-30	9000330385	Max. 19	2IFpR19/66 2.0Ah 6.4V	20-55	45-125	3	60	3
AI03-30	9000330385	Max. 19	2IFpR19/66 2.0Ah 6.4V	20-55	45-125	3	60	3
AI03-15	9000310185	Max. 19	2IFpR19/66 2.0Ah 6.4V	20-55	45-125	3	60	1.5
AI03-30/MC/ST.	9000330366	Max. 19	2IFpR19/66 2.0Ah 6.4V	20-55	45-125	3	60	3
AI01-30/MC/ST	9000330366	Max. 19	2IFpR19/66 2.0Ah 6.4V	20-55	45-125	3	60	3
AI01-30/ST	9000330386	Max. 19	2IFpR19/66 2.0Ah 6.4V	20-55	45-125	3	60	3
AI03-15/MC/ST	9000310166	Max. 19	2IFpR19/66 2.0Ah 6.4V	20-55	45-125	3	60	1.5
AI03-30/ST.	9000330386	Max. 19	2IFpR19/66 2.0Ah 6.4V	20-55	45-125	3	60	3
AI03-15/ST	9000310186	Max. 19	2IFpR19/66 2.0Ah 6.4V	20-55	45-125	3	60	1.5
AI03-30/MC/DA	9000330367	Max. 19	2IFpR19/66 2.0Ah 6.4V	20-55	45-125	3	60	3
AI03-15/MC/DA	9000310167	Max. 19	2IFpR19/66 2.0Ah 6.4V	20-55	45-125	3	60	1.5
AI03-30/DA	9000330387	Max. 19	2IFpR19/66 2.0Ah 6.4V	20-55	45-125	3	60	3
AI03-15/DA	9000310187	Max. 19	2IFpR19/66 2.0Ah 6.4V	20-55	45-125	3	60	1.5
AI02-30LFP7302-S20	9000330385	Max. 19	2IFpR19/66 2.0Ah 6.4V	20-55	45-125	3	60	3
AI05-30/MC	9000530465	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	20-55	73-200	5	60	3
AI05-15/MC	9000510365	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	20-55	73-200	5	60	1.5
AI05-30	9000530485	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	20-55	73-200	5	60	3
AI05-15	9000510385	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	20-55	73-200	5	60	1.5
AI05-30/MC/ST	9000530466	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	20-55	73-200	5	60	3
AI05-15/MC/ST	9000510366	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	20-55	73-200	5	60	1.5

CERTIFICATE

No. U6 102263 0047 Rev. 00

AI05-30/ST	9000530486	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	20-55	73-200	5	60	3
AI05-15/ST	9000510386	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	20-55	73-200	5	60	1.5
AI05-30/MC/DA	9000530467	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	20-55	73-200	5	60	3
AI05-15/MC/DA	9000510367	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	20-55	73-200	5	60	1.5
AI05-30/DA	9000530487	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	20-55	73-200	5	60	3
AI05-15/DA	9000510387	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	20-55	73-200	5	60	1.5
AI04-30LFP7304-S20	9000530465	Max. 21	2IFpR19/66-2 4.0Ah 6.4V	20-55	73-200	5	60	3

**Tested
according to:**

EN 61347-1:2015/A1:2021
EN 61347-2-7:2012/A2:2022

**Production
Facility(ies):**

102263